




NPC/TRELLBORG  
S206-58L  
PIPE ADAPTER  
2 REQUIRED



NPC/TRELLBORG  
CGA-48A  
HDPE PIPE ADAPTER  
2 REQUIRED



48" HDPE SHOWING  
LENGTH AND PLACEMENT  
OF NPC CGA-48A ADAPTER  
1 REQUIRED



## NOTES:

### 1). EXCAVATION SPECIFICATIONS:


LENGTH 28'-0"  
WIDTH 9'-0"  
DEPTH BELOW INLET 5'-1" (61")

### 2). THE DON CHAPIN COMPANY MAY MAKE CHANGES TO THE DESIGN AND OR TO THE DIMENSIONS WITHOUT NOTICE. PLEASE CONTACT THE DON CHAPIN PRE-CAST DIVISION WHENEVER NECESSARY TO CONFIRM DESIGN CRITERIA.

### 3). INLET AND OUTLET PIPES ARE FITTED WITH A-LOK PRODUCTS, INC. QUIK-LOK SERIES WATERTIGHT PIPE-TO-TANK CONNECTIONS

### 4). THIS IS ALSO AVAILABLE AS AN H20 RATED ASSEMBLY

### 5). INTEGRAL TOP TO BODY DESIGN



DON CHAPIN PRE-CAST  
2735 BOLSA RD.  
HOLLISTER, CA 95023  
(831) 630-1042  
(831) 630-5763

## PRE-CAST CONCRETE SEAMLESS SEPTIC BATTERY TANK ASSEMBLY CAPACITY 5000 GALLONS MODEL IPS5000



2/11/10