

NOTE: THIS TANK CAN BE CAST WITH ORENCO RISER ADAPTERS (24" OR 30") INSTEAD OF CONCRETE PLUGS. PLEASE ASK FOR DETAILS WHEN PLACING ORDER.

NOTE: INLET AND OUTLET PIPES ARE FITTED WITH WATERTIGHT A-LOK PIPE CONNECTIONS (STANDARD).

NOTES:

1). EXCAVATION SPECIFICATIONS:

LENGTH 9' - 0"

WIDTH 9' - 0"


DEPTH BELOW INLET 5' - 4"

2). DON CHAPIN PRE-CAST MAY MAKE CHANGES TO THE DESIGN AND OR TO THE DIMENSIONS WITHOUT NOTICE. PLEASE CONTACT DON CHAPIN PRE-CAST WHENEVER NECESSARY TO CONFIRM DESIGN CRITERIA.

3). CERTIFIED ENGINEERING IS AVAILABLE UNPON REQUEST.

4). THIS IS ALSO AVAILABLE AS AN H20 RATED ASSEMBLY

5). INTEGRAL TOP TO BODY DESIGN



THE DON CHAPIN COMPANY
PRE-CAST DIVISION
2735 BOLSA RD.
HOLLISTER, CA 95023
831-630-1042
831-630-5763 FAX

PRE-CAST CONCRETE WATER TIGHT
SEPTIC TANK
CAPACITY 1500 GALLONS
MODEL IPS1500



2/12/09